

ONFLOOR® STONECARE SYSTEM



ONFLOOR® **StoneCare System** is designed for restoration and maintenance of marble, tile, terrazzo, stone and concrete. This versatile floor machine is available in 10", 17", 20", and 24"; and can also be used for standard floor scrubbing, stripping and polishing applications. The 10" model can be used in small and confined areas, and is available with optional short handle. ONFLOOR® StoneCare Vacuum is designed for special applications, requiring both solution pressure spraying and concurrent liquid recovery. It is excellent for use in marble/stone restoration, extraction, spill cleanup, for rinsing and vacuuming applications.



ONFLOOR® STONECARE SYSTEM

Oversized Handle Grips

For operator's comfort.

Heavy-Duty Switch

Set in a die cast aluminum switch box, which won't chip or rust.

4 Gallon Plastic Solution Tank

Dispenses liquid for scrubbing, polishing and diamond cutting. Won't rust or corrode.

Weight System

Includes two 10 lb. discs and three 25 lb. discs, allows operator to adjust surface pressure in 10 and 25 lb. increments while staying within recommended amperage range.

Enhanced High Torque, Triple Planetary Gear System

Permanently lubricated, operates at 140 RPM with 1½ HP motor.

Reinforced Aluminum Apron with Lift Handle

for added strength and rigidity, also shields the transport wheels to prevent damage.

Built-In AMP Meter

Allows for constant monitoring of current draw and selection of the correct weight.

Flexible Dual Triggers

Left or right hand operation, non-conductive with built-in safety lockouts to prevent accidental startup.

50 Ft. Power Cord

3-wire safety yellow with water-resistant jacket.

Wheel Support System

Extra heavy-duty reinforced six point cast aluminum.

Diamond Disc Driver with the Unique Slurry Guard

Includes five quick change diamond mounting pads and skirt to contain slurry.



SPECIFICATIONS

Motor:	120V, 1½ HP, 60 Hz, DC Rectified for AC Operation w/Carbon Brush Wear Indicator Light
Gears:	3 Idler - 11.1 Ratio
Drive Speed:	140 RPM
Power Cord:	50 Ft. 14/3 Wire Grounded, Safety Yellow
OSL-10C	235121
Brush Size:	10"
Wheels:	3" Transport
OSL-17E DLX	235083
Brush Size:	17"
Wheels:	5" Transport
OSL-20E DLX	235156
Brush Size:	20"
Wheels:	5" Transport
OSL-24E DLX	235105
Brush Size:	24"
Wheels:	4" Transport



Order No:	235172
Vacuum Motor:	120 Volt, 2 Stage 2.3 HP By-Pass; 115 CFM-Waterlift 110"
Current:	11.0 AMPS
Sound Level:	77dB
Power Cord:	30 Ft. 14/3 Wire Grounded Safety Yellow
Vacuum Tank:	20 Gallon Recovery Capacity
Ring Tank:	10 Gallon Recovery Capacity
Pump:	100 PSI

MADE IN THE U.S.A. BY ONFLOOR TECHNOLOGIES®

